

238584



{In Archive} GE - Powerex Cross-hole tests

David A Eckhardt

to:

John H Williams, JD, jm, Robert Alvey

08/19/2008 04:18 PM

Cc:

Isabel Rodrigues

Hide Details

From: David A Eckhardt <daeckhar@usgs.gov>

To: John H Williams <jhwillia@usgs.gov>, "JD" <DoughertyJN@cdm.com>, "jm" <MayoJJ@cdm.com>, Robert Alvey/R2/USEPA/US@EPA

Cc: Isabel Rodrigues/R2/USEPA/US@EPA

History: This message has been forwarded.

Archive: This message is being viewed in an archive.

2 Attachments



B32_Xhole1.pdf B32_Xhole2.pdf

Here is a preliminary look at the two cross-hole tests at Powerex, with a 385-ft radial spacing between wells.

To summarize:

Test 1 (June 2008)

B-32-D3 had 18.048 ft displacement in source well

B-31-D3 had 0.023 ft displacement in observation well, **no packer**

Test 2 (Aug 2008)

B-32-D3 24.301 ft displacement in source well

B-31-D3 had 0.028 ft displacement in observation well, **with packer**

The T results are similar, but Test 1 without the packer appears to be a more typical type curve at the observation

well.
Comments?

—Dave

David A.V. Eckhardt	tel: (607)266-0217 x3018
U.S. Geological Survey	cell: (607)227-4182
30 Brown Road	fax: (607)266-0521
Ithaca, NY 14850-1573	email: daeckhar@usgs.gov